



Grey Block Product Guide

VICTORIA




Block Product Guide


100 Series

Grey Blocks


Hollow 100mm Series 60 minutes fire rating ($f_{uc} \geq 10\text{MPa}$ FRL = 60 Srf ≤ 22.5)




10.01AG*
Standard Hollow
11.1 kg
149 per pallet




10.02AG
Three Quarters
8.7 kg
192 per pallet




10.03AG
Half
5.5 kg
252 per pallet



10.31AG*
Standard Solid
14.2 kg
139 per pallet




10.32AG
Three Quarter
10.2 kg
192 per pallet




10.71AG*
Half Height Hollow
5.6 kg
300 per pallet

Fire Rated Blocks


Solid 100mm Series 120 minutes fire rating ($f_{uc} \geq 10\text{MPa}$ FRL = 90 Srf ≤ 22.6)v




10.31FR*
Standard Solid
14.2 kg
139 per pallet



10.32FR
Three Quarter
10.2 kg
192 per pallet



10.33FR
Half
6.8 kg
252 per pallet




10.34FR
Quarter
3.3 kg
504 per pallet

120 Series

Fire Rated Blocks

Reduced Core 120mm Series

90 minutes fire rating ($f_{uc} \geq 8\text{MPa}$ FRL = 90 Srf ≤ 22.6)




12.01FR*
Reduced Core
13.4 kg
120 per pallet


Note:
1 in 5 "universal" for ½ or ¾, to bolster on site.

Bricks

90 minutes fire rating



Core Cast Brick*
3.3 kg
500 per pallet
 $\geq 10\text{ MPa}$ Ash Grey



Quick Brick*
6.8 kg
250 per pallet

Note:

- * These products are sold by the full pallet (A part pallet will incur a part pallet make-up fee)
- Lead time required for Melbourne metropolitan delivery of Grey Block is 1-3 working days
- f_{uc} – characteristic unconfined compressive strength
- FRL – Fire resistance level


Block Product Guide

150 Series


Grey Blocks

Hollow 150mm Series


60 minutes fire rating ($f_{uc} \geq 15\text{MPa}$ FRL = 60 Srf ≤ 22.5) suitable for concrete filling




15.42UNV*
Universal Hollow
12.8 kg
120 per pallet




Note:
→ Each pallet of 15.42UNV is packaged with 1 in 4 Universal 2 Closed Ends




15.01AG*
Standard Hollow
12.5 kg
120 per pallet




15.02AG
Three Quarter
10.5 kg
128 per pallet




15.03AG
Half
6.9 kg
192 per pallet




15.22AG
Corner Block
12.3 kg
108 per pallet




15.12AG
Bond Beam
17.8 kg
96 per pallet



15.71AG*
Half Height Hollow
7.5 kg
216 per pallet




15.48AG*
'H' Block
14.0 kg
120 per pallet




15.45
Cleanout
10.4 kg
120 per pallet

Solid 150mm Series

120 minutes fire rating ($f_{uc} \geq 15\text{MPa}$ FRL = 120 Srf ≤ 20)




15.83AG
Half Height Solid (with frog)
10.0 kg
168 per pallet




15.85AG
Half (with frog)
5.1 kg
336 per pallet

Light Weight Structural


120 minutes fire rating ($f_{uc} \geq 15\text{MPa}$ FRL = 120 Srf ≤ 22.6) suitable for concrete filling




15.20LWS*
Light Weight
11.6 kg
144 per pallet




Note:
→ Each pallet of 15.20LWS is packaged with 1 in 4 Universal 2 Closed Ends



15.02LWS
Three Quarter
8.7 kg
128 per pallet



15.03LWS
Half
6.0 kg
192 per pallet



15.22LWS
Corner Block
10.6 kg
108 per pallet


Note:

- *These products are sold by the full pallet (A part pallet will incur a part pallet make-up fee)
- Lead time required for Melbourne metropolitan delivery of Grey Block is 1-3 working days
- f_{uc} – characteristic unconfined compressive strength
- FRL – Fire resistance level


Block Product Guide

200 Series Grey Blocks


Hollow 200mm Series 60 minutes fire rating ($f_{uc} \geq 15\text{MPa}$ FRL = 60 Srf ≤ 22.5) suitable for concrete filling




20.42UNV*
Channel/Notch Block
14.3 kg
108 per pallet




20.02AG
Three Quarter
13.4 kg
96 per pallet



20.03AG
Half
8.6 kg
144 per pallet




20.01AG*
Standard Hollow
15.9 kg
90 per pallet




20.71AG*
Half Height Hollow
7.3 kg
162 per pallet


Note:
Each pallet of 20.42UNV is packaged with 1 in 3 Universal 1 Closed End




5031AG 190x390
Capping
6.7 kg
216 per pallet




20.12AG
Lintel Bond Beam
22.6 kg
72 per pallet




20.48AG*
'H' Block
14.2 kg
90 per pallet



20.45
Cleanout
11.4 kg
108 per pallet




20.18
Deep Lintel
14.7 kg
108 per pallet




20.03C
Curved Wall
6.3 kg
180 per pallet

Fire Rated Blocks


Light Weight Structural 120 minutes fire rating ($f_{uc} \geq 15\text{MPa}$ FRL = 120 Srf ≤ 22.6) suitable for concrete filling



20.20LWS*
Light Weight
12.8 kg
108 per pallet



20.02LWS
Three Quarter
12.2 kg
96 per pallet




20.03LWS
Half
7.6 kg
144 per pallet


Note:
Each pallet of 20.20LWS is packaged with 1 in 3 Universal 2 Closed Ends

300 Series Grey Blocks


Hollow 300mm Series 240 minutes fire rating when grout filled ($f_{uc} \geq 15\text{MPa}$ FRL = 240 Srf ≤ 36) suitable for concrete filling




30.48AG*
'H' Block
19.6 kg
72 per pallet
 $f'_{uc} \geq 15\text{MPa}$




20.02AG
Half and End
13.4 kg
96 per pallet




10.32AG
Three Quarter
10.2 kg
192 per pallet



30.01AG
Standard
20.3 kg
72 per pallet



30.45
Cleanout
16.30 kg
60 per pallet



30.18
Deep Lintel
17.8 kg
85 per pallet


Note:

- * These products are sold by the full pallet (A part pallet will incur a part pallet make-up fee)
- Lead time required for Melbourne metropolitan delivery of Grey Block is 1-3 working days
- f'_{uc} – characteristic unconfined compressive strength
- FRL – Fire resistance level


Block Product Guide

Mortarless Block System


200mm Series



Stretcher Unit*
17.5 kg
60 per pallet



End & Corner Unit
16.9 kg
60 per pallet




Half Unit
Capping
9.4 kg
100 per pallet

Note:

- * These products are sold by the full pallet (A part pallet will incur a part pallet make-up fee)
- Lead time required for Melbourne metropolitan delivery of Grey Block is 1-3 working days
- f'uc – characteristic unconfined compressive strength
- FRL – Fire resistance level

Accessories



Mortar Sand Grey
1.4 tonne
Bulk Bag



Bulk Grout
1.4 tonne
Bulk Bag




Lime Juice
5.2 kg
5 Litre bottle



GP Cement
20kg
72 per pallet



Lime
20kg
54 per pallet



50.45
Biscuit & Spring
4.1 kg
120 per pallet

Joint Reinforcement



50mm
Used for 100mm Series
Block
Note: Sold in bundles of 20 x 2.9mtr lengths



100mm
Used for 150mm Series
Block



150mm
Used for 200mm Series
Block

Mortar Additive



20 Litre Drum
20 litres will lay up to
1750 blocks

Block & Brick Estimator

Block & Brick Estimator	Full Height	Half Height	Quarter Height	Standard Brick	Quick Brick
Masonry unit face size (L x H mm)	390 x 190	390 x 90	390 x 40	230 x 76	230 x 162
No. Units per m ²	12.5	25	50	50	25

Material Quantities for 1m³ of Mortar

- For every 800 full height blocks (390 long x 190 high) or 64m² of wall, approximately 1m³ of mortar mix is required, allowing for wastage.
- There are 12.5 full blocks per square metre of wall surface area.

	Grey Block		Designer Range	
	Mix in 1:1:6 proportions		Mix in 1:5 proportions	
M3	Cement	14 bags (20kg each)	Cement	16 bags (20kg each)
	Lime	5 bags (20kg each)	Designer Range Additive	8 litres
	Sand	1.2m ³	Sand	1.2m ³
	Mix in 1:0.5:4:5 proportions		Mix in 1:4 proportions	
M4	Cement	18 bags (20kg each)	Cement	20 bags (20kg each)
	Lime	3 bags (20kg each)	Designer Range Additive	10 litres
	Sand	1.2m ³	Sand	1.2m ³

Note: Use clean, sharp sand and allow 20% for bulking. Sand, Cement, lime and mortar additive available from National Masonry®. Can be delivered on same truck as product.

Grout for Core Filling

The correct grout specification (mix design) is critical to achieving the structural design of a reinforced wall. The grout used to fill the cores of blockwork walls should be specified as follow:

- Grout to comply with AS3700 Clause 11.7.
- Characteristic Compressive Strength 20MPa.
- Cement content not less than 300kg/m³.
- Round aggregate (if any) not more than 10mm.
- Clean sand (1.2m³)
- A pouring consistency which ensures that the cores are completely filled and the reinforcement completely surrounded without segregation of the constituents.

Control Joints

Because of temperature variations and the shrinkage in a concrete masonry wall after construction, it is necessary to provide control joints in blockwork at a max spacing of 6m and at points of potential cracking, e.g. beside openings and at large steps in wall or footing.

- Joint width is 10mm for panels up to 6000mm long.
- Joint sealants should be applied towards the end of construction to minimise the effect of panel movement.

Core Fill Quantities - 1m ³ Grout	
Block Type	Number of Blocks
15.48, 15.42, 15.20	190
15.101	200
20.42, 20.20	120
20.101	125
20.48	100
30.48	65
Mortarless 200	125

Accessories

Sand, Cement, Lime, Mortar Additive and Masonry Mesh are available from National Masonry® and can be delivered conveniently on same truck. Ring office for competitive pricing.

Online Booking Pickup

Use our Pallet Collection Form on our website.

www.nationalmasonry.com.au

Call to Arrange Pickup

Call your local branch during office hours.

9361 6443 or 9361 6400



Contact

To find your closest National Masonry® stockist, to receive brochures or to learn more about our products, call us or visit our website at www.nationalmasonry.com.au



Victoria

Riding Boundary Road,
Deer Park
Melbourne VIC 3023
Phone: (03) 9361 6400
Fax: (03) 9363 6008

melbourne.sales@nationalmasonry.com.au

South Queensland

62 Industrial Avenue,
Wacol
Brisbane QLD 4076
Phone: (07) 3271 9292
Fax: (07) 3271 1815

brisbane.sales@nationalmasonry.com.au

Gold Coast

663 Pine Ridge Road,
Biggera Waters
Gold Coast QLD 4216
Phone: (07) 5552 3300
Fax: (07) 5552 3399

labrador.sales@nationalmasonry.com.au

North Queensland

6 David Muir Street,
Slade Point
Mackay QLD 4740
Phone: (07) 4955 1155
Fax: (07) 4955 4130

mackay@nationalmasonry.com.au

New South Wales

65 Burleigh Street,
Toronto
Lake Macquarie NSW 2283
Phone: (02) 4088 1888
Fax: (02) 4088 1899

toronto.sales@nationalmasonry.com.au

Colour variations occur from batch to batch. Colours shown are indicative only and should not be used for final selection. Products ordered should be chosen from actual samples current at the time of order and are subject to availability. Photographs in this brochure are only representative of National Masonry® products and the appearance and effect that may be achieved by their use. Samples, brochures and displays should be viewed as a guide only. Customers should ensure all delivered products are acceptable, and any concerns about products are made prior to laying. All prices are subject to availability and can be withdrawn or varied without notice. © Copyright National Masonry Pty Ltd - all rights reserved 2013. Gardenwall® & Keystone® are registered trademarks of Keystone® Retaining Wall Systems Inc, use under licence by National Masonry®. National Masonry®, the National Masonry® logo, nationalmasonry.com.au, if these and other National Masonry Pty Ltd trade marked terms are marked on their first occurrence in this information with a trade mark symbol (® or ™), these symbols indicate Australian registered or common law trade marks owned by National Masonry® Pty Ltd at the time this information was published. Such trade marks may also be registered or common law trade marks in other countries. Other product, company or service names may be trade marks or service marks of others. National Masonry Pty Ltd ABN 94 155 064 136. Correct as at 30/11/2023.