

Product Information Sheet



- Description:** 190mm 'Control Joint' light weight
- Product code:** 20.09 / 20.10
- Dimensions:** 190 x 190 x 390 mm / 190 x 190 x 190 mm (H x W x L)
Category DW4 as per AS 4455.1, determined in accordance with AS/NZS 4456.3.
- Strength:** Characteristic Unconfined Compressive Strength ≥ 15 MPa
- Fire Resistance:** 120 / 120 / 120 min ($S_{rf} \leq 21.14$)
240/240/240 (core-filled, $S_{rf} < 15$ if unreinforced) (DTS AS3700 Sec. 6)
- Durability:** Exposure Grade (determined by AS/NZS 4456.10 - Resistance to Salt Attack)
- Weight:** 14.2 Kg / 8.5 Kg $\pm 5\%$
- No. Per pallet:** 72 / 72 Units (combination pallet)
- No. Per m²:** 12.5 / 25 Units



Manufactured to AS/NZS 4455.1 & 4455.3:2008

* Fire Resistance Levels as per Exova Warringtonfire Assessment Report #28339-00 & AS3700.

** Durability as per BMRL Research Laboratory test certificate #8263, AS/NZS 4456.10 Method B.

The information above is for general description purposes only.

04/06/2020 - subject to change without notice.