

# Product Information Sheet



<b>Description:</b>	290mm 'H-block' light weight
<b>Product code:</b>	30.48
<b>Dimensions:</b>	190 x 290 x 390 mm (H x W x L) Category DW4 as per AS 4455.1, determined in accordance with AS/NZS 4456.3.
<b>Strength:</b>	Characteristic Unconfined Compressive Strength $\geq$ 15 MPa
<b>Fire Resistance:</b>	120 / 120 / 120 min ( $S_{rf} \leq 21.14$ ) in a 300 series block wall. 240/240/240 (core-filled, $S_{rf} < 15$ if unreinforced) (DTS AS3700 Sec. 6)
<b>Durability:</b>	Exposure Grade (determined by AS/NZS 4456.10 - Resistance to Salt Attack)
<b>Weight:</b>	14.52 Kg $\pm$ 5%
<b>No. Per pallet:</b>	72 Units
<b>No. Per m<sup>2</sup>:</b>	12.5 Units



Manufactured to AS/NZS 4455.1 & 4455.3:2008

\* Fire Resistance Levels as per Exova Warringtonfire Assessment Report #28339-00 & AS3700.

\*\* Durability as per BMRL Research Laboratory test certificate #8263, AS/NZS 4456.10 Method B.

The information above is for general description purposes only.

29/10/2019 - subject to change without notice.