

PRODUCT INFORMATION SHEET

SPEEDBLOX® System, hollow light weight 200 series

Strength: Characteristic Unconfined Compressive Strength ≥ 15 MPa

Durability: Exposure Grade

Stretcher (Product Code MSPDBLWHNAT00LW):

Dimensions: 190 x 190 x 400 mm (W x H x L, module) (+/- Tolerance to AS 4455.1)

Weight: 12.1 Kg $\pm 10\%$ **No. Per Pallet:** 90 Units **No. Per m²:** 12.5 Units

Corner (Product Code MCON20LANATCRLW):

Dimensions: 190 x 190 x 400 mm (W x H x L, module) (+/- Tolerance to AS 4455.1)

Weight: 14.34 Kg $\pm 10\%$ **No. Per Pallet:** 90 Units **No. Per m²:** 12.5 Units

Half (Product Code MCON20LANATHALW):

Dimensions: 190 x 190 x 200 mm (W x H x L, module) (+/- Tolerance to AS 4455.1)

Weight: 6.94 Kg $\pm 10\%$ **No. Per Pallet:** 180 Units **No. Per m²:** 25 Units

Minimum face shell thickness 30mm



Manufactured to AS/NZS 4455.1:2008.

** Durability as per BMRL Research Laboratory
test certificate #8263, AS/NZS 4456.10 Method B.

The information above is for general description purposes only.
08/03/2021 - subject to change without notice.