







# ELPAVE and HEADER



## ELPAVE (LIP80)

Units per sq metre: 27  
Units per Pallet: 270  
Weight per unit (Kg): 6.5



## HEADER (IP80HEAD)

Units per sq metre: 41  
Units per Pallet: 500  
Weight per unit (Kg): 4.14



Natural (NAT)

## Overview ELPAVE SYSTEM - ELPAVE and HEADER

Segmental ELPAVE paving system: ELPAVE engineered for high volume traffic, heavy loading and poor foundation support with HEADER complimenting the edges.

National Masonry ELPAVE's unparalleled performance stems from the innovative interlocking shape, high strength and long-term durability of every unit. ELPAVE's interlocking shape actually becomes stronger under traffic flow, locking together to provide a superior pavement with proven long-term stability.

ELPAVE system provides all of the advantages of a cement based product including resistance to rutting, resistance to oil and petrol attack, plus the strength to withstand high point loadings, and combines them with all of the advantages of a flexible segmental pavement, including the elimination of shrinkage cracking and joint stepping, while maintaining ready access to underground services and easy rehabilitation.

ELPAVE system also provides high abrasion and skid resistance.

National Masonry® ELPAVE system offers engineers, architects, developers and town planners, an engineered, high performance paving system that has been specifically designed for heavy wheeled, high volume traffic and poor foundation support conditions.

National Masonry® ELPAVE system provides outstanding durability and strength for applications such as heavy haulage and container terminals, airports, service stations and industrial sites.

## Recommended for



All high volume, high traffic applications.

- Outstanding performance ✓
- Proven durability ✓
- Excellent skid resistance ✓
- Attractive & cost effective ✓



L shaped ELPAVE WITH HEADERS at the edge.

<b>Dimensions (ELPAVE/HEADER) (W x H x L):</b>	<b>105 x 80 x 237mm / 110 x 80 x 220mm</b>
<b>Tolerance (height/plan):</b>	<b>±2mm/±1.5mm</b>
<b>Manufacturing Standard:</b>	<b>AS/NZS 4455</b>
<b>Content:</b>	<b>Cement, sand, stone aggregate</b>
<b>Characteristic Breaking Load:</b>	<b>10 kN minimum</b>
<b>Characteristic Flexural Strength:</b>	<b>4 MPa minimum</b>
<b>Abrasion Resistance:</b>	<b>7 maximum (AS/NZS 4456.9)</b>
<b>Slip Resistance:</b>	<b>P5 (AS/NZS 4586, Slider 55)</b>
<b>CMAA Shape Category:</b>	<b>Type A</b>
<b>Colour:</b>	<b>Natural Grey</b>

## Pallet Return



All pallets remain the property of National Masonry®

### Online Booking Pickup

Use our Pallet Collection Form on our website.

[www.nationalmasonry.com.au](http://www.nationalmasonry.com.au)

### Call to Arrange Pickup

Call Victoria branch during office hours.

**03 9361-6443**

## Contact

To find your closest National Masonry® stockist, to receive brochures or to learn more about our products, call us or visit our website at [www.nationalmasonry.com.au](http://www.nationalmasonry.com.au)

### Victoria

Riding Boundary Road,  
Deer Park

Melbourne VIC 3023

Phone: (03) 9361 6400

Fax: (03) 9363 6008

[melbourne.sales@nationalmasonry.com.au](mailto:melbourne.sales@nationalmasonry.com.au)

### South Queensland

62 Industrial Avenue,  
Wacol

Brisbane QLD 4076

Phone: (07) 3271 9292

Fax: (07) 3271 1815

[brisbane.sales@nationalmasonry.com.au](mailto:brisbane.sales@nationalmasonry.com.au)

### Gold Coast

663 Pine Ridge Road,  
Biggera Waters

Gold Coast QLD 4216

Phone: (07) 5552 3300

Fax: (07) 5552 3399

[labrador.sales@nationalmasonry.com.au](mailto:labrador.sales@nationalmasonry.com.au)

### North Queensland

6 David Muir Street,  
Slade Point

Mackay QLD 4740

Phone: (07) 4955 1155

Fax: (07) 4955 4130

[mackay@nationalmasonry.com.au](mailto:mackay@nationalmasonry.com.au)

### New South Wales

65 Burleigh Street,  
Toronto

Lake Macquarie NSW 2283

Phone: (02) 4088 1888

Fax: (02) 4088 1899

[toronto.sales@nationalmasonry.com.au](mailto:toronto.sales@nationalmasonry.com.au)

