

# **SAFETY DATA SHEET**

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name CONCRETE MASONRY PRODUCTS

Synonyms MASONRY PRODUCTS

1.2 Uses and uses advised against

Uses BASIC CONSTRUCTION MATERIAL ● CONSTRUCTION MATERIAL ● MASONRY CONSTRUCTION ●

**PAVEMENT MATERIAL** 

1.3 Details of the supplier of the product

Supplier name NATIONAL MASONRY PTY LTD (VIC)

Address Riding Boundary Road, P.O. Box 345, Deer Park, Melbourne, Victoria, 3023, AUSTRALIA

**Telephone** (03) 9361 6400 **Fax** (03) 9363 6008

Website <a href="http://www.nationalmasonry.com.au">http://www.nationalmasonry.com.au</a>

1.4 Emergency telephone numbers

**Emergency** (03) 9361 6400

## 2. HAZARDS IDENTIFICATION

# 2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

## 2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

# 2.3 Other hazards

The solid product as supplied is classified as non-hazardous under normal conditions and does not present an inhalation, ingestion, skin, or eye hazard. However, dust created when the product is cut, grinded and machined may contain crystalline silica some of which may be respirable (particles small enough to go into deep parts of the lung when breathed in).

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

## 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
QUARTZ (CRYSTALLINE SILICA)	14808-60-7	238-878-4	10 to 60%
PIGMENT(S)	-	-	1 to 10%
PORTLAND CEMENT	65997-15-1	266-043-4	1 to 10%
AGGREGATE	-	-	10 to 30%
WATER	7732-18-5	231-791-2	1 to 10%
ALKYLTRIALKOXY SILANE/SILOXANE	-	-	<5%
FATTY ACID SALT(S)	-	-	<3%

## 4. FIRST AID MEASURES



SDS Date: 04 Mar 2022 Revision No: 4

### PRODUCT NAME CONCRETE MASONRY PRODUCTS

### 4.1 Description of first aid measures

Eye (Dust exposure) Flush gently with running water, irrigating under eyelids. Seek medical attention if irritation

develops.

Inhalation (Dust exposure) If inhaled remove from contaminated area. Apply artificial respiration if not breathing.Skin (Dust exposure) Gently flush affected areas with water. Seek medical attention if irritation develops.

**Ingestion** Due to product form and application, ingestion is considered unlikely.

First aid facilities Eye wash facilities and safety shower should be available, particularly when dust is generated.

## 4.2 Most important symptoms and effects, both acute and delayed

This product may present a hazard if cut or drilled with dust generation. CAUTION: Repeated exposure to dust may cause lung fibrosis (silicosis).

### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

## 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

## 5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

### 5.3 Advice for firefighters

No fire or explosion hazard exists.

## 5.4 Hazchem code

None allocated.

# 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

# 6.2 Environmental precautions

Prevent product from entering drains and waterways.

# 6.3 Methods of cleaning up

If spilt, collect and reuse where possible. Avoid generating dust. As for dust, it is best cleaned up by vacuum device to avoid generating airborne dust. Wetting before sweeping up dust may assist in dust control.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

# 7. HANDLING AND STORAGE

# 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

# 7.2 Conditions for safe storage, including any incompatibilities

Ensure material is adequately labelled and protected from physical damage. Avoid generating dust.

## 7.3 Specific end uses

No information provided.

ChemAlert.

SDS Date: 04 Mar 2022

Revision No: 4

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## 8.1 Control parameters

## **Exposure standards**

Ingredient	Reference	TWA		STEL	
ingredient	Kelerence	ppm	mg/m³	ppm	mg/m³
Portland cement	SWA [AUS]		10		
Portland cement	SWA [Proposed]		1		
Quartz (respirable dust)	SWA [AUS]		0.05		
Quartz (respirable dust) (Precautionary advice)	WorkSafe VIC		0.02		

### **Biological limits**

No biological limit values have been entered for this product.

### 8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction

ventilation is recommended. Wet where possible. Maintain dust levels below the recommended exposure

standard.

**PPE** 

Eye / Face If cutting or sanding with potential for dust generation, wear dust-proof goggles.

**Hands** Wear leather or cotton gloves.

**Body** Not required under normal conditions of use.

Respiratory If cutting, sanding or drilling with potential dust generation, wear a Class P1 (Particulate) respirator, consider

using vacuum/ extraction system or control dust using dust supressing methods such as wetting.





## 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

**Appearance** SOLID Odour SLIGHT ODOUR **Flammability** NON FLAMMABLE **NOT RELEVANT** Flash point **NOT AVAILABLE Boiling point NOT AVAILABLE Melting point NOT AVAILABLE Evaporation rate** pН **NOT AVAILABLE** Vapour density **NOT AVAILABLE** Relative density **NOT AVAILABLE** Solubility (water) **INSOLUBLE** NOT AVAILABLE Vapour pressure Upper explosion limit **NOT RELEVANT NOT RELEVANT** Lower explosion limit Partition coefficient NOT AVAILABLE Autoignition temperature NOT AVAILABLE **Decomposition temperature** NOT AVAILABLE **Viscosity** NOT AVAILABLE **Explosive properties NOT AVAILABLE** Oxidising properties NOT AVAILABLE **Odour threshold** NOT AVAILABLE

9.2 Other information

Bulk density 1200 kg/m³ to 2300 kg/m³

# 10. STABILITY AND REACTIVITY



SDS Date: 04 Mar 2022 Revision No: 4

#### PRODUCT NAME **CONCRETE MASONRY PRODUCTS**

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with strong acids (e.g. hydrochloric acid).

## 10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

# 11. TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects

**Acute toxicity** This product is expected to be of low toxicity. Ingestion is considered unlikely due to product form.

Mechanical irritant. Prolonged or repeated contact may result in mild irritation due to mechanical action. Skin

Mechanical irritant. Due to product form and nature of use, the potential for exposure is reduced. Product Eye

may only present a hazard if material is cut, drilled or sanded with dust generation, which may result in

mechanical irritation.

Sensitisation Not classified as causing skin or respiratory sensitisation.

Mutagenicity Not classified as a mutagen.

Carcinogenicity Adverse health effects, usually associated with long term exposure to high respirable crystalline silica quartz

dust levels are not anticipated due to product form. This product may only present a hazard if rocks are cut or drilled with dust generation. Respirable crystalline silica quartz is classified as carcinogenic to humans (IARC

Reproductive Not classified as a reproductive toxin.

STOT - single Dust can be generated during cutting of the product. Dusts are mechanical irritants that may cause throat

irritation. exposure

Adverse health effects, usually associated with long term exposure to high respirable crystalline silica quartz STOT - repeated exposure dust levels are not anticipated due to the product form. This product may present a hazard if cut or drilled

with dust generation. CAUTION: Repeated exposure to dust may cause lung fibrosis (silicosis).

Not applicable for solids. **Aspiration** 

## 12. ECOLOGICAL INFORMATION

## 12.1 Toxicity

The substance is inert and there is no evidence of significant toxicity.

## 12.2 Persistence and degradability

Being inorganic, the substance will not biodegrade.

### 12.3 Bioaccumulative potential

The substance is inert and will not be absorbed and accumulate in tissues.

## 12.4 Mobility in soil

No information provided.

# 12.5 Other adverse effects

The main component/s of this product are not anticipated to cause any adverse effects to plants or animals.

# 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Waste disposal Reuse where possible. Dispose of in accordance with local regulations.

ChemAlert.

SDS Date: 04 Mar 2022 Revision No: 4

## PRODUCT NAME CONCRETE MASONRY PRODUCTS

**Legislation** Dispose of in accordance with relevant local legislation.

# 14. TRANSPORT INFORMATION

# NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

## 14.5 Environmental hazards

No information provided.

# 14.6 Special precautions for user

Hazchem code None allocated.

# 15. REGULATORY INFORMATION

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals (GHS Revision 7).

Inventory listings AUSTRALIA: AllC (Australian Inventory of Industrial Chemicals)

All components are listed on AIIC, or are exempt.

## 16. OTHER INFORMATION

# Additional information

# PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

### **HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



SDS Date: 04 Mar 2022

Revision No: 4

## PRODUCT NAME CONCRETE MASONRY PRODUCTS

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide
IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

## Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmtglobal.com

[ End of SDS ]

Page 6 of 6



SDS Date: 04 Mar 2022

Revision No: 4