


Last Update: 15/05/2025

TECHNICAL DATA SHEET		
Product Code:	CONNEX 200 ST	
Product Description:	CONNEX MORTARLESS STRETCHER 200 BLOCK	
Dimensions:	200 x 200 x 400 mm (W x H x L)	
Compressive Strength:	Unconfined compressive strength f_{uc} : 15 MPa	
Density:	2100 kg/m ³	
Fire:	Fire Resistance Level (FRL): -/-/240 minutes Core Filled	
Max Slenderness Ratio for FRL Structural Adequacy:	36.0 for FRL 240 minutes (when core filled)	
Material Thickness for FRL Insulation:	N/A	
Sound:	Weighted Sound Reduction Index (R_w): 45	
R Value (Bare Block)	N/A	
Water Absorption:	7.7% by mass	
Salt Attack Resistance:	General Purpose	
Weight:	17.5 kg	
No. per pallet:	72	
No. per m ²	12.5	
No. per Tonne:	57	

Fire Resistance Levels as per Section 6, AS 3700

Manufactured in accordance to AS/NZS 4455

Dimensions Tolerance +/- 2 mm for Length, Width and Height

Quality Assurance AS/NZS ISO 9001

The test results shown have been recorded in laboratory conditions. Results achieved in the field may vary due to differences in construction techniques or material variations.

For detailed specification to meet your precise requirements, expert advice should be obtained from National Masonry.

The physical properties on the Technical data sheet will also apply to the following products:

Connex CR – (Dimensions: 200 x 200 x 400mm)

Connex HA – (Dimensions: 200 x 200 x 200mm)

Subject to change without notice